



Absen Holdings (Hong Kong) Company Limited

Unit 1302, Level 13, Landmark North, 39 Lung Sum Avenue, Sheung Shui, New Territories, Hong Kong

rita.zhang@absen.com ; Http:// www.absen.com

TEL: 86-13825271485 By: Rita Zhang

Absen-PL3.9W Lite



Screen Configuration

Module			
Dimensions (w x h) (mm)	250 X 250	Resolution (w x h)	64 X 64
Pixel pitch (mm)	3.9	Pixel Density (pixels/m2)	65746
Pixel Configuration	SMD 3in1		
Standard Panel			
Dimensions(w x h x d)(mm)	500 x 500 x 87	Module Quantity	4
Physical Resolution (w x h)	128 x 128	Physical Pixels (total)	16384
Weight/Panel (kg)	9.5	Material	Die Casting Aluminum
Certificate		Power (Max./Avg.)(W/m²)	600/200

Display Data

Item	Width	Height	Total:
Panel Quantity(pcs)	16	10	160
Panel Area Dimension(sqmm)	8,000	5,000	40,000
Display Resolution(dots)	2048	1280	2,621,440
Total Net Weight (kgs)	1520.0		
Total Average Power(watts)	8000	Total Max Power(watts)	24000
Parameter	Value	Parameter	Value
Brightness	4000 cd/m²	Viewing Angle	140/120
Minimum Viewing Distance	3.9 meters	Gray scale	14 Bit
Contrast ratio	4000:1	Refresh rate	1920 HZ
Color temperature	6500 K	Module Maintenance	F&R
Input Voltage	100-240 V	PSU & Others Maintenance	R
Input power frequency	50 or 60 HZ	IP RATING	IP65/IP54
Operating temperature	- 20~ + 50	Operating humidity	10% -90%
Control distance	CAT5 cable: < 100 m; Multi-mode fiber:300 m; Single-mode fiber:10km		